Reference: Client:

Project: Consultant:

Location: Contractor:

Submitted by: Date:



Model RAPI

Fire-rated Access Door Wingnut Closure

Application:

CVS-SAFE4 Fire-rated Duct Access Doors range are tested in accordance to BS476 Part24:1987 (ISO6944) and EN 1366-1 for up to 4-hours. These access doors are designed to be installed into fire-rated ductwork for the purpose of internal inspection and access for cleaning purposes without compromising the rating of the ductwork. The Access Doors provide efficient and secure service access to critical areas in ducts for a wide range of commercial, industrial, and residential which can be installed in both new and retrofit applications.

All CVS-SAFE4 marked products carry third party Certification and Local AHJ approval.

Standard Construction:

	Standard	Optional
Frame Material	40x1.5mm thick channel section frame, height suited to thickness of insulation	Galvanised Steel Stainless Steel Mild Steel
Door Material	18-Gauge sheet steel with 5mm lip formed on all sides	Galvanised Steel Stainless Steel Mild Steel
Lock Mechanism	Wingnuts & Bolt Closure	
Type of Installation of Door to Duct Skin	4.8mm Steel Rivets	Welded
Insulation	25mm Rock Wool	50mm or 75mm Rock Wool
Gasket & Sealant	Ceramic Gasket with bead of fire-rated sealant	
Accessories	Welded Handle	Bolted Handle
Hourly Rating	2-hours	4-hours
Finish	Mill Finish	Coating - Red Oxide or Galvanic Heat Resistant

Minimum & Maximum Sizes:

Model	Minimum Single Section	Maximum Single Section
RAPI - Insulated	6" x 6"	40" x 40"
Bolted Panel	(150 x 150)	(1000 x 1000)

All dimensions shown in inches, parentheses () indicate millimeters.

Optional Construction:

Round Construction (Consult factory for saddles installation on round ducts) Safety Steel Wire




STANDARDS MET:

BS Standard: BS476 Part 24, BS5588 (BS9999) EN & Other Standards: EN1366-1, ISO6944


NFPA Standards: 96



Model RAPI - Insulated Bolted Panel




Model RAPI - Detail



Wingnut Washer Ceramic Gasket with bead of fire-rated sealant Bolts welded to frame Insulation packing Fastened to duct skin with 4.8mm steel revits or bolts

Model RAPI - Dimensions



Size of the frame shall be C or D in mm

Submittal

As part of our continuous improvement program, we reserve the right to make further improvements without notice.