ARBO

ARBOSEAL INTUMESCENT TAPE

Arboseal Intumescent Tape is a flat section, preformed Intumescent strip based upon synthetic rubbers and carefully chosen fire resistant materials. It deforms under moderate pressure and has appreciable surface tack and recovery. When subject to flame, Arboseal Intumescent Tape will intumesce (expand and char) blocking the passage of fire and smoke.

MAIN APPLICATIONS

Recommended for use in HVAC metal ducting, glazing internal and external FD30 timber fire doors and screens.

NB: Not recommended for external use without a sealant capping (please contact Adshead Ratcliffe Technical Service Department for further information.)

Not recommended for use in expansion joints.



TECHNICAL DATA	
Colours	Teak, White
Application Temperature:	+ 5º C to + 50º C
Service Temperature:	- 25º C to + 50º C
Chemical Resistance:	Fair resistance to most dilute acids and alkalis, vegetable oils and alcohol. Poor resistance to hydrocarbon solvents.
UV Resistance:	Good
Service Life:	20 years +



HEAITH AND SAFFTY

No particular hazards with this product but please consult Material Safety Data Sheet for full information

PACKAGING

Size: 15mm x 3 mm x 12 metres per reel.

STORAGE LIFE

12 months in original unopened packaging stored in a cool, dry place out of direct sunlight

ACCESSORIES

Cleaners

Arbo Cleaner No.17-1 Litre Tin (Xylene based - not suitable for use with plastics or delicate finishes) Arbo Cleaner No. 16 - 1 Litre Tin (Alcohol Based)

SPECIFICATION COMPLIANCE

BS476 Part 22:1987;

Warrington Report Number: C118002

TRADA Report Number: IT349

IMPORTANT: The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.

